

## Cutting Tips



### Oxy/Acetylene

These two piece tips are very popular. Their flame characteristics, plus the ease of cleaning, make them ideal for Plumbers, Panel Beaters and other Contractors.

#### To suit 362 Cutting Att.

	Size	Precision Series
3690	00AC	Cuts 0-6mm Steel
3690	OAC	Cuts 6-13mm Steel
3690	1AC	Cuts 13-25mm Steel
3690	2AC	Cuts 25-75mm Steel

AVAILABLE  
IN POP  
HANG  
SELL



### Oxy/Acetylene

This Professional tip offers exceptionally quick starting for the operator. Combined with the ability to pull apart for cleaning. The flat seating allows easy reseating on-site with a rub with wet/dry - **a very unique product.** This flat seating tip greatly reduces the occurrence of tip popping. Precise gas flutes control the amount of gas being used.

Made  
in  
Europe



#### To suit 492 Cutt.Att., 142 & 624L Torches

	Size	Professional Series
6290	000	Cuts 0-5mm Steel (One pce copper)
	00AC	Cuts 5-10mm Steel
	0AC	Cuts 10-15mm Steel
	1AC	Cuts 15-25mm Steel
	2AC	Cuts 25-50mm Steel
	3AC	Cuts 50-100mm Steel
	4AC	Cuts 100-175mm Steel
	5AC	Cuts 175-250mm Steel
	6AC	Cuts 250-300mm Steel

**NOTE:** Standard 5mm Hose does limit good cutting to 100mm. For thicker steel, use larger diameter Hose.