

Cutting Tips

Oxy/Propane/LPG/Natural Gas

Opens up avenues for the Contractor who is using LPG/Propane as his fuel gas. A high performance product, which will give quick starts and quality cutting.

To suit 362 Cutting Attachment

	Size	Precision
3690	00P	Cuts 0-6mm Steel
3690	0P	Cuts 6-13mm Steel
3690	1P	Cuts 13-25mm Steel
3690	2P	Cuts 25-75mm Steel



AVAILABLE
IN POP
HANG
SELL

Professional Oxy/Propane/LPG

The design of these Tips is superb and adds a new dimension to cutting, using Oxy/ LPG, Propane, Natural Gas. Develops very **quick starts** and also **precise control** over the amount of gas used. Every Tip is flame is tested before leaving the factory.

To suit 1492FHC, 492F Cutt. Att., 142F & 624FL.

Size Professional

000NX	Cuts 0- 5mm Steel
00NX	Cuts 5-10mm Steel
0NX	Cuts 10-15mm Steel
1NX	Cuts 15-25mm Steel
2NX	Cuts 25-50mm Steel
3NX	Cuts 50-75mm Steel
4NX	Cuts 75-150mm Steel
5NX	Cuts 150-200mm Steel
6NX	Cuts 200-300mm Steel



Made
in
Europe

Professional Oxy/Natural Gas

NFF Cutting tips specially designed for Natural gas use. Providing extra heat in the start up process.

1NFF	15-25mm
2NFF	25-50mm
3NFF	50-75mm
4NFF	75-150mm
5NFF	150-200mm
6NFF	200-300mm